



Truefashion Projector GCGM

RS700B LED20 930PW PSU NB BK

Lens

The Truefashion Projector is ideal for the retail segment with its attractive outlook design, excellent quality of light and dedicated light recipe, as well as system connectivity, to create a comfortable ambience and impressive shopping experience to stimulate the sales for retail customers.

Warnings and Safety

- 3 years

Product data

General Information	
Lamp colour code	930 warm white
Optical cover/lens type	Lens
Control interface	-
Protection class IEC	Safety class II (II)
CE mark	CE mark
Number of products on MCB (16 A type B)	1
Light source engine type	LED
Operating and Electrical	
Input Voltage	220 to 240 V
Input frequency	50 or 60 Hz
Power factor (min.)	0.97

Controls and Dimming	
Dimmable	No
Mechanical and Housing	
Housing material	Aluminium
Optical cover/lens material	Polymethyl methacrylate
Optical cover/lens finish	-
Overall height	70 mm
Overall diameter	96 mm
Colour	Black
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	-

Truefashion Projector GCGM

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1685 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	79 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>90
Initial input power	21 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-15 to +35 °C
---------------------------	---------------

Product Data

Full product code	911401520171
Order product name	RS700B LED20 930PW PSU NB BK
Order code	911401520171
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401520171
SAP net weight (piece)	0.330 kg



Dimensional drawing



Spotlight/ projector LED

