



Truefashion Projector GCGM

RS700B LED20 930PW PSU MB BK

Lens

The Truefashion Projector is ideal for the retail segment with its attractive outlook design, excellent quality of light and dedicated light recipe, as well as system connectivity, to create a comfortable ambience and impressive shopping experience to stimulate the sales for retail customers.

Warnings and Safety

- 3 years

Product data

General Information		Controls and Dimming	
Lamp colour code	930 warm white	Dimmable	No
Optical cover/lens type	Lens	Mechanical and Housing	
Control interface	-	Housing material	Aluminium
Protection class IEC	Safety class II (II)	Optical cover/lens material	Polymethyl methacrylate
CE mark	CE mark	Optical cover/lens finish	-
Number of products on MCB (16 A type B)	1	Overall height	70 mm
Light source engine type	LED	Overall diameter	96 mm
Operating and Electrical		Colour	Black
Input Voltage	220 to 240 V	Approval and Application	
Input frequency	50 or 60 Hz	Ingress protection code	IP20 [Finger-protected]
Power factor (min.)	0.97	Mech. impact protection code	-

Truefashion Projector GCGM

Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	1685 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	79 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>90
Initial input power	21 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-15 to +35 °C
---------------------------	---------------

Product Data

Full product code	911401520271
Order product name	RS700B LED20 930PW PSU MB BK
Order code	911401520271
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401520271
SAP net weight (piece)	0.330 kg



Dimensional drawing



Spotlight/ projector LED

