



Truefashion Projector GCGM

RS700B LED20 930PC PSU MB WH

Lens -

The Truefashion Projector is ideal for the retail segment with its attractive outlook design, excellent quality of light and dedicated light recipe, as well as system connectivity, to create a comfortable ambience and impressive shopping experience to stimulate the sales for retail customers.

Warnings and Safety

- 3 years

Product data

General information		Controls and dimming	
Lamp colour code	930 warm white	Dimmable	No
Optical cover/lens type	Lens	Mechanical and housing	
Control interface	-	Housing material	Aluminium
Protection class IEC	Safety class II (II)	Optical cover/lens material	Polymethyl methacrylate
CE mark	CE mark	Optical cover/lens finish	-
Number of products on MCB (16 A type B)	1	Overall height	70 mm
Light source engine type	LED	Overall diameter	96 mm
Operating and electrical		Colour	White RAL 9003
Input Voltage	220 to 240 V	Approval and application	
Input frequency	50 or 60 Hz	Ingress protection code	IP20 [Finger-protected]
Power factor (min.)	0.97	Mech. impact protection code	-

Truefashion Projector GCGM

Initial performance (IEC compliant)

Initial luminous flux (system flux)	1577 lm
Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	74 lm/W
Lamp colour temperature	3000 K
Colour Rendering Index	>90
Initial input power	21 W
Power consumption tolerance	+/-10%

Application conditions


Ambient temperature range	-15 to +35 °C
---------------------------	---------------

Product data

Full product code	911401520571
Order product name	RS700B LED20 930PC PSU MB WH
Order code	911401520571
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401520571
Net Weight (Piece)	0.330 kg



Dimensional drawing



RS700B LED20 930PC PSU MB WH

