



# Tango G4 LED Flood

**BVP433 LED470/CW 220~240V 345W NB GM**

5700 K

Philips Tango G4 LED flood lighting is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

## Warnings and Safety

- please pay attention to the mounting instructions

## Product data

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	345 W
Power Factor (Fraction)	0.9
Connection	Flying leads/wires
Cable	Cable 1.5 m without plug
General Information	
Driver included	Yes

Lighting Technology	LED
Light Technical	
Luminous Flux	47,000 lumen
Correlated Color Temperature (Nom)	5700 K
Luminous Efficacy (rated) (Nom)	136 lm/W
Color rendering index (CRI)	>70
Light source color	757 cool white
Optical cover/lens type	Polycarbonate bowl/cover

# Tango G4 LED Flood

Temperature	
Ambient temperature range	-40 to +50 °C

Controls and Dimming	
Dimmable	No
Control interface	-

Mechanical and Housing	
Housing Material	Aluminum die cast
Optical cover/lens material	Polycarbonate
Housing Color	Gray
Overall length	523 mm
Overall width	559 mm
Overall height	71 mm
Dimensions (Height x Width x Depth)	71 x 559 x 523 mm

Approval and Application	
Ingress protection code	IP66 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK08 [5 J vandal-protected]
Protection class IEC	Safety class I


CE mark	
CE mark	CE mark

Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%
Power consumption tolerance	+/-10%

Product Data	
Full product code	871951454076700
Order product name	BVP433 LED470/CW 220~240V 345W NB GM
EAN/UPC - Product	8719514540767
Order code	911401604507
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	1
Material number (12NC)	911401604507
Full product name	BVP433 LED470/CW 220~240V 345W NB GM
EAN/UPC - Case	8719514540767



## Dimensional drawing

