



Tango G4 LED Flood

BVP432 LED204/CW 220~240V 150W SMB GM

5700 K

Philips Tango G4 LED flood lighting is the 4th generation of the Tango LED family. A new range lighting that delivers higher efficacy and has an optimized windage area, and less weight thanks to its technical design. This product introduction is the ideal solution for a wide range of area lighting and recreational sports lighting applications. It incorporates the latest LED light source, one-piece optical system, heat sink and driver into a compact and robust housing that meets globally-recognized safety standards. Its specially-designed heat sink incorporates aesthetics and functionality to ensure excellent reliability. Powered by LED technology, Tango G4 LED floodlights deliver superior performance and a longer lifetime, bringing area lighting to a whole new level.

Warnings and Safety

- please pay attention to the mounting instructions

Product data

Operating and Electrical		Lighting Technology	
Input Voltage	220 to 240 V		LED
Line Frequency	50 or 60 Hz	Light Technical	
Input Frequency	50 or 60 Hz	Luminous Flux	20,400 lumen
Power Consumption	150 W	Correlated Color Temperature (Nom)	5700 K
Power Factor (Fraction)	0.9	Luminous Efficacy (rated) (Nom)	136 lm/W
Connection	Flying leads/wires	Color rendering index (CRI)	>70
Cable	Cable 1.5 m without plug	Light source color	757 cool white
		Optical cover/lens type	Polycarbonate bowl/cover
General Information			
Driver included	Yes		

Tango G4 LED Flood

Temperature

Ambient temperature range -40 to +50 °C

Controls and Dimming

Dimmable No

Control interface -

Mechanical and Housing

Housing Material Aluminum die cast

Optical cover/lens material Polycarbonate

Housing Color Gray

Overall length 347 mm

Overall width 414 mm

Overall height 77 mm

Dimensions (Height x Width x Depth) 77 x 414 x 347 mm

Approval and Application

Ingress protection code IP66 [Dust penetration-protected, jet-proof]

Mech. impact protection code IK08 [5 J vandal-protected]

Protection class IEC Safety class I

CE mark CE mark

Initial Performance (IEC Compliant)

Luminous flux tolerance +/-10%

Power consumption tolerance +/-10%

Product Data

Full product code 871951454045300

Order product name BVP432 LED204/CW 220~240V 150W SMB GM

Order code 911401689306

Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 1

Material number (12NC) 911401689306

Full product name BVP432 LED204/CW 220~240V 150W SMB GM

EAN/UPC - Case 8719514540453



Dimensional drawing

