



Greenspace Flex

RS378Z M55 D78 R-R AJ D

Accessory

GreenSpace Flex is a performance portfolio dedicated to the hospitality segment for GC/GM countries. With a modular design concept, the light engines and different trims have multiple combinations to satisfy diversified customer requirements.

Product data

General Information	
Beam angle of light source	- °
Lamp colour code	-
Optic type	No [-]
Optical cover/lens type	No [-]
Control interface	-
Cable	-
Protection class IEC	-
Glow-wire test	60030 [Temperature 600 °C, duration 30 s]
Flammability mark	NO [-]
CE mark	-
ENEC mark	-
Warranty period	3 years
Constant light output	No
Number of products on MCB (16 A type B)	-
Light source engine type	-
Operating and Electrical	
Input Voltage	- V
Input frequency	- Hz

Power factor (min.)	-
Mechanical and Housing	
Housing material	Aluminium
Optical cover/lens material	-
Fixation material	Aluminium
Optical cover/lens finish	-
Overall length	0 mm
Overall width	0 mm
Overall height	52 mm
Overall diameter	85 mm
Colour	White
Dimensions (height x width x depth)	52 x 0 x 0 mm (2 x 0 x 0 in)
Approval and Application	
Ingress protection code	- [-]
Mech. impact protection code	IK04 [0.5 J standard plus]
Initial Performance (IEC Compliant)	
Lamp colour temperature	- K
Colour Rendering Index	-


Greenspace Flex

Initial input power	- W
Application Conditions	
Ambient temperature range	-20 to +45 °C
Maximum dimming level	Not applicable
Product Data	
Full product code	911401721702

Order product name	RS378Z M55 D78 R-R AJ D
Order code	911401721702
SAP numerator – quantity per pack	1
Numerator – packs per outer box	48
SAP material	911401721702



Dimensional drawing



RS378Z M55 D78 R-R AJ D

