



HF-Performer II for PL-T/C/R/L/TL5C lamps

HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V

HF-Performer EII PL-T/C/R/T5c is a sustainable, slim and high-frequency electronic ballast for a wide range of CFL- ni applications. It is ideal for applications where high energy efficiency is required. The HF-Performer EII range has a robust design, meets all relevant international safety and performance standards and is energy-efficient (CELMA EEI A2).

Product data

| General Information | | Temperature | |
|--|--------------|---------------------------------|---|
| Number of Lamps | 1 piece/unit | Ambient temperature range | -25 °C to 50 °C |
| Operating and Electrical | | T-Case Lifetime (Nom) | 75 °C |
| Input Voltage | 220 to 240 V | T-Case Maximum (Max) | 75 °C |
| Line Frequency | 50 to 60 Hz | Approval and Application | |
| Input Frequency | 50 to 60 Hz | Ingress protection code | IP20 [Finger-protected] |
| Inrush Current Width | 0.25 ms | Energy Efficiency Index | A2 |
| Inrush Current Peak (Max) | 18 A | Safety Standard | IEC 61347-2-3 |
| Number of Products on MCB (16A Type B) (Nom) | 28 | Environmental Standard | ISO 14001 |
| Wiring | | Approval Marks | CE marking ENEC certificate VDE-EMV certificate |
| Connector Type Input Terminals | Insert | Product Data | |
| Connector Type Output Terminals | Insert | Full product code | 871150091397530 |
| | | Order product name | HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V |
| | | Order code | 913700630766 |

HF-Performer II for PL-T/C/R/L/TL5C lamps

| | |
|---------------------------------|---|
| Numerator - Quantity Per Pack | 1 |
| Numerator - Packs per outer box | 12 |
| Material number (12NC) | 913700630766 |
| Full product name | HF-P 1 22-42 PL-T/C/L/TL5C EII 220-240V |

| | |
|----------------|---------------|
| EAN/UPC - Case | 8711500913982 |
|----------------|---------------|



Dimensional drawing

| Product | D1 | C1 | A1 | A2 | B1 | B2 |
|---|--------|---------|----------|---------|---------|---------|
| HF-P 1 22-42 PL-T/C/L/ TL5C EII 220-240V | 4.5 mm | 30.0 mm | 103.0 mm | 93.5 mm | 67.0 mm | 57.5 mm |

