



DynaVision Programmable Xtreme for CDMe

HID-DV PROG Xt 210 CDMe/CPO C2 208-277V

Highly reliable and flexible electronic drivers for MASTERColour CDMe MW lamps; designed to save on energy costs via integrated controls and to reduce maintenance costs thanks to 80,000 hour lifetime and integrated lightning protection. The DynaVision Programmable product family is the perfect basis for any sort of lighting management solution.

Product data

General Information		Connector Type	WAGO series 804
Number of Lamps	1 piece/unit		
Operating and Electrical		Temperature	
Input Voltage	208-240-277 V	Ambient temperature range	-30 °C to 50 °C
Line Frequency	50 to 60 Hz	T-Case Lifetime (Nom)	80 °C
Input Frequency	50 to 60 Hz	Controls and Dimming	
Power Factor 50% Load (Min)	0.98	Control Interface	PROG
Earth Leakage Current (Max)	0.7 mA	Mechanical and Housing	
Inrush Current Width	4 ms	Housing	C2
Input Current (Nom)	1.11 A	Approval and Application	
Inrush Current Peak (Max)	4 A	Surge Protection (Common/Differential)	EN61547 (L-L 2kV, L-G 4kV), 10 kV TIL
Number of Products on MCB (16A Type B) (Nom)	13	Safety Standard	IEC 607, 609, 926, 928 [No Standard for HID Lamp drivers exists. Requirements in these
Wiring			
Cable Length From Device to Lamp	3 m		

DynaVision Programmable Xtreme for CDMe

	standards to be used if considered relevant for the product.]
Environmental Standard	ISO 14001
Approval Marks	F-Marking CE marking ENEC certificate VDE-EMV certificate
Product Data	
Full product code	871829122269900
Order product name	HID-DV PROG Xt 210 CDMe/CPO C2 208-277V

Order code	913700676966
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	6
Material number (12NC)	913700676966
Full product name	HID-DV PROG Xt 210 CDMe/CPO C2 208-277V
EAN/UPC - Case	8718291222705

Dimensional drawing

^?

Product	D1	C1	A1	A2	B1	B2
HID-DV PROG Xt 210 CDMe/CPO C2 208-277V	4.8 mm	58.0 mm	169.0 mm	156.0 mm	100.0 mm	81.5 mm

