



# Electronic ignitor for HID lamp circuits

## SI 51 Plus

HID ignitors for parallel systems


### Product data

General information	
Application code	SI 51 Plus
Operating and electrical	
Input Voltage	220 to 240 V
Input frequency	50 to 60 Hz
Ignition type	Parallel
Ignition voltage (max.)	0.75 kV
Ignition voltage (min.)	0.58 kV
Response voltage	190 V
Mains voltage performance (AC)	-8%+6%
Mains voltage safety (AC)	-10%+10%
Power losses (nom.)	0.5 W
Wiring	
Ballast contact wire cross section	0.50-2.50 mm <sup>2</sup>
Connector type	Screw
Temperature	
T-ambient (max.)	75 °C

T-ambient (min.)	-20 °C
T-Case maximum (max.)	80 °C
Mechanical and housing	
Housing	Akulon S223
Approval and application	
Approval marks	CE marking ENEC certificate
Product data	
Full product code	697013372887100
Order product name	SI 51 Plus
EAN/UPC – product	6970133728871
Order code	913710011113
SAP numerator – quantity per pack	1
Numerator – packs per outer box	48
SAP material	913710011113
Net Weight (Piece)	0.049 kg

## Electronic ignitor for HID lamp circuits

### Dimensional drawing



Product	C1	A1	A2	B1	D1
SI 51 Plus	38.5 mm	85.5 mm	65.0 mm	41.5 mm	4.3 mm

SI 51 Plus

