



HF-Performer III for TL-D lamps

HF-P 158 TL-D III 220-240V 50/60Hz IDC

HF-Performer III TLD is a sustainable, slim and high-frequency electronic ballast for TL-D fluorescent lamps. It is ideal for applications where high energy efficiency is required. The HF-Performer III range has a robust design, meets all relevant international safety and performance standards and is energy-efficient (CELMA EEI A2).

Product data

General Information		Connector Type Output Terminals	
Number of Lamps	1 piece/unit	Connector Type Output Terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]
Operating and Electrical		Temperature	
Input Voltage	220 to 240 V	Ambient temperature range	-25 °C to 60 °C
Line Frequency	50 to 60 Hz	T-Case Lifetime (Nom)	80 °C
Input Frequency	50 to 60 Hz	T-Case Maximum (Max)	80 °C
Inrush Current Width	0.25 ms	Mechanical and Housing	
Power Factor (Fraction)	0.99	Housing	L 280x30x28
Inrush Current Peak (Max)	18 A	Approval and Application	
Number of Products on MCB (16A Type B) (Nom)	28	Ingress protection code	IP20 [Finger-protected]
Wiring		Energy Efficiency Index	A2 BAT
Connector Type Input Terminals	WAGO 251 universal connector [Suitable for both automatic wiring (ALF and ADS) and manual wiring]	Safety Standard	IEC 61347-2-3
		Environmental Standard	ISO 14001
		Approval Marks	CE marking ENEC certificate VDE-EMV certificate

HF-Performer III for TL-D lamps

Product Data	
Full product code	872790091170100
Order product name	HF-P 158 TL-D III 220-240V 50/60Hz IDC
Order code	913713031866
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12

Material number (12NC)	913713031866
Full product name	HF-P 158 TL-D III 220-240V 50/60Hz IDC
EAN/UPC - Case	8727900911701



Dimensional drawing

A2

Product	D1	C1	A1	A2	B1
HF-P 158 TL-D III 220-240V 50/60Hz IDC	4.2 mm	28.0 mm	280.0 mm	265.0 mm	30.0 mm

