



# HF-Selectalume II for TL5 lamps

## HF-S 154 TL5 II 220-240V 50/60Hz

HF-Selectalume II is the most cost-effective, reliable, slim and affordable fluorescent solution, with highly disruptive technology for energy saving, system flexibility and unsurpassed performance. The cost-saving HF-Selectalume II has a robust design which meets all relevant international safety and performance standards. HF-Selectalume II is intended for use with indoor lighting fixtures such as spotlights, downlights and recessed luminaires, which are largely used in office, retail, industry, hotel, restaurant and other applications where control devices are installed with occasional On/Off switching activity

### Product data

General Information		T-Case Lifetime (Nom)		75 °C	
Number of Lamps	1 piece/unit	T-Case Maximum (Max)		75 °C	
Operating and Electrical		Mechanical and Housing			
Input Voltage	220 to 240 V	Housing	L 280x30x21		
Line Frequency	50 to 60 Hz	Approval and Application			
Input Frequency	50 to 60 Hz	Ingress protection code	IP20 [Finger-protected]		
Earth Leakage Current (Max)	0.5 mA	Energy Efficiency Index	A2 BAT		
Inrush Current Width	0.25 ms	Approval Marks	F-Marking CE marking ENEC certificate CCC certificate C-Tick certificate PSB certification TISI marking SIRIM approval CB Certificate CCC certificate VDE-EMV certificate		
Inrush Current Peak (Max)	20 A	Product Data			
Wiring		Full product code	872790090561800		
Connector Type Input Terminals	WAGO 744 connector	Order product name	HF-S 154 TL5 II 220-240V 50/60Hz		
Connector Type Output Terminals	WAGO 744 connector [Suitable for manual wiring]				
Temperature					
Ambient temperature range	-15 °C to 50 °C				

## HF-Selectalume II for TL5 lamps

Order code	913713033666
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material number (12NC)	913713033666
Full product name	HF-S 154 TL5 II 220-240V 50/60Hz

EAN/UPC - Case	8727900905618
----------------	---------------



### Dimensional drawing

A2

Product	D1	C1	A1	A2	B1
HF-S 154 TL5 II 220-240V 50/60Hz	4.1 mm	28.0 mm	280 mm	265 mm	30.0 mm

