



# PAR38

## PAR38 80W E27 230V PAR38 Spot 12D 1CT/12

Pressed-glass 121 mm diameter reflector lamps of high luminous intensity


### Product data

General Information	
Cap base	E27 [ E27]
Burning Position	UNIVERSAL [ Any/Universal]
Nominal lifetime (nom.)	2000 h
Switching cycle	8,000X
Rated Lifetime	2000 h
Light Technical	
Technical Beam Angle (Nom)	12 °
Lamp Luminous Flux (Nom)	655 lm
Luminous intensity (max.)	4700 cd
Beam description	Spot
Rated beam angle	12 °
Colour Temperature, horizontal (Nom)	2700 K
Colour Rendering Index, horiz (Nom)	100
Luminous flux in 90° cone (rated)	655 lm
Operating and Electrical	
Power (Rated) (Nom)	80.0 W
Starting time (nom.)	0.0 s
Warm-up time to 60% light (nom.)	instant full light
Power factor (nom.)	1
Voltage (Nom)	230 V

Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Bulb shape	PAR38 [ PAR 4.75 inch/121mm]
Approval and Application	
Energy consumption kWh/1,000 hours	80 kWh
Product Data	
Full product code	871150060037000
Order product name	PAR38 80W E27 230V PAR38 Spot 12D 1CT/12
EAN/UPC – product	8711500600370
Order code	923810244214
SAP numerator – quantity per pack	1
Numerator – packs per outer box	12
SAP material	923810244214
SAP net weight (piece)	319.000 g
ILCOS code	IPAR-80-230-E27-121/12

# PAR38

## Dimensional drawing



Product	D (max)	C (max)
PAR38 80W E27 230V PAR38 Spot 12D 1CT/12	123 mm	137 mm

PAR38 80W E27 230V SP

## Photometric data

