



MASTER PL-L 4 Pin

MASTER PL-L 55W/865/4P 1CT/25

Energy-saving compact fluorescent lamps Compact long-arc low-pressure mercury discharge lamp Envelope consists of 2 parallel fluorescent tubes

Warnings and Safety

- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position as well as applied control gear
- Shorter lamp life when often switching and not well pre-heated electrodes
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

Product data

General Information	
Cap base	2G11 [2G11]
Life to 50% failures preheat (nom.)	20000 h
System description	High Frequency [High Frequency (HF)]
LSF preheat 2,000 hours rated	99 %
LSF preheat 4,000 hours rated	99 %
LSF preheat 6,000 hours rated	98 %
LSF preheat 8,000 hours rated	97 %
LSF preheat 16,000 hours rated	82 %
LSF preheat 20,000 hours rated	50 %
	Sphere

Light Technical	
Colour Code	865 [CCT of 6,500 K]
Lamp Luminous Flux 25°C EL (Nom)	4600 lm
Lamp Luminous Flux (Nom)	4800 lm
Colour Designation	Cool Daylight

Chromaticity coordinate X (nom.)	0.313
Chromaticity coordinate Y (nom.)	0.337
Colour Temperature, horizontal (Nom)	6500 K
Lamp Luminous Efficacy EM (Nom)	82 lm/W
Colour Rendering Index,horiz (Nom)	80
LLMF 2000 h Rated	94 %
LLMF 4000 h Rated	93 %
LLMF 6000 h Rated	92 %
LLMF 8000 h Rated	91 %
LLMF 12000 h Rated	90 %
LLMF 16000 h Rated	88 %
LLMF 20000 h Rated	87 %


Operating and Electrical	
Power (Rated) (Nom)	55.3 W
Lamp current (nom.)	0.525 A

MASTER PL-L 4 Pin

Temperature	
Design temperature (nom.)	30 °C
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-base information	4P
Approval and Application	
Energy Efficiency Class	G
Mercury (Hg) content (max.)	2 mg
Mercury (Hg) content (nom.)	2.0 mg
Energy consumption kWh/1,000 hours	56 kWh

	423315
Product Data	
Full product code	871150026170040
Order product name	MASTER PL-L 55W/865/4P 1CT/25
EAN/UPC – product	8711500261700
Order code	927908786570
SAP numerator – quantity per pack	1
Numerator – packs per outer box	25
SAP material	927908786570
SAP net weight (piece)	134.000 g
ILCOS code	FSDH-55/65/1B-L/P-2G11


Dimensional drawing



PL-L 55W/865/4P HF

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
MASTER PL-L 55W/865/4P 1CT/25	39.0 mm	18.0 mm	509.2 mm	535 mm	541.6 mm

Photometric data



Lightcolour /865

Lightcolour /865

MASTER PL-L 4 Pin

