



# GreenSpace Flex

## RS378B P15 940 PSR-E 1-10V NB M55

--

GreenSpace Flex is performance portfolio dedicated to Hospitality segment for GC/GM countries. With modular design concept, the light engines and different trims could have multiply of combination to satisfy diversified customer's requirement.

### Product data

General Information	
Light source engine type	LED
Light Technical	
Luminous Flux	1,140 lumen
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	76 lm/W
Color rendering index (CRI)	>90
Light source color	940 neutral white
Optical cover/lens type	-
Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Input Frequency	50 or 60 Hz
Power Consumption	15 W
Power Factor (Fraction)	0.9
Number of products on MCB of 16 A type B	-

Temperature	
Ambient temperature range	-20 to +45 °C
Controls and Dimming	
Dimmable	Yes
Control interface	KNX
Mechanical and Housing	
Housing Material	Aluminum Alloy
Optical cover/lens material	-
Housing Color	Dark gray
Optical cover/lens finish	-
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK04 [0.5 J standard plus]
Protection class IEC	Safety class II
CE mark	-
Initial Performance (IEC Compliant)	
Luminous flux tolerance	+/-10%

# Greenspace Flex

Power consumption tolerance	+/-10%
<b>Product Data</b>	
Full product code	911401540971
Order product name	RS378B P15 940 PSR-E 1-10V NB M55
Order code	911401540971
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	48
Material number (12NC)	911401540971
Full product name	RS378B P15 940 PSR-E 1-10V NB M55



## Dimensional drawing

