



Pureline Slim EX

RC780B LED26S-4000 PSD W7L120 OD SI EX

The PureLine Slim family of luminaires gives you compromise-free office illumination. It is a perfect solution for office application and general indoor area lighting with Sleek profile which helps Declutter the ceilings. The range brings together high-flux lighting with a homogeneous optical system without making any concessions on energy efficiency design.

Warnings and Safety

- Meant for Indoor Application Only. Should not be used in outdoor environment.

Product data

General Information	
Driver included	Yes
Light source engine type	LED
Value ladder	Performance
Warranty period	1 years
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Luminous Flux	2,600 lumen
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (rated) (Nom)	114 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	- degree(s)
Light source color	840 neutral white
Optic type	-
Optical cover/lens type	Polycarbonate Diffuser
Luminaire light beam spread	-

Operating and Electrical	
Line Frequency	50 or 60 Hz
Input Voltage	220 to 240 V
Power Consumption	23 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	0 to +45 °C
Controls and Dimming	
Dimmable	Yes
Control interface	DALI
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Housing Color	Aluminum and gray
Mounting device	Mounting bracket

Pureline Slim EX

Optical cover/lens shape	Flat
Overall length	1,196 mm
Overall width	89 mm
Overall height	78.5 mm
Dimensions (Height x Width x Depth)	79 x 89 x 1196 mm
Material	Aluminum

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	Surge protection level until 2 kV
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Initial chromaticity	<5
----------------------	----

Power consumption tolerance	+/-10%
-----------------------------	--------

Over Time Performance (IEC Compliant)

Median useful life L70B50	50,000 hour(s)
---------------------------	----------------

Product Data

Order product name	RC780B LED26S-4000 PSD W7L120 OD SI EX
Order code	919515898138
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	919515898138
Full product name	RC780B LED26S-4000 PSD W7L120 OD SI EX

Dimensional drawing

Installation Instructions PHILIPS
PURE LINE SLIM RECESSED

TYPE	A	B	Voltage	Frequency
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz
RC780B LED26S-4000 PSD W7L120 OD SI EX	78	89	220-240V~	50/60Hz

Product Dimensions 2 Feet
2000, 89, 78.5

Product Dimensions 4 Feet
4000, 89, 78.5

ATTENTION: Install by a qualified electrician and wired in accordance with local IEC electrical regulations or the national requirements.

