



Pureline Slim EX

RC780X LED22S-6500 PSD W6L120 OD SI EX

The PureLine Slim family of luminaires gives you compromise-free office illumination. It is a perfect solution for office application and general indoor area lighting with Sleek profile which helps Declutter the ceilings. The range brings together high-flux lighting with a homogeneous optical system without making any concessions on energy efficiency design.

Warnings and Safety

- Meant for Indoor Application Only. Should not be used in outdoor environment.

Product data

General Information	
Driver included	Yes
Light source engine type	LED
Value ladder	Performance
Warranty period	1 years
Flammability mark	For mounting on normally flammable surfaces
Light Technical	
Luminous Flux	2,200 lumen
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	116 lm/W
Color rendering index (CRI)	>80
Beam angle of light source	- degree(s)
Light source color	865 cool daylight
Optic type	-
Optical cover/lens type	Polycarbonate Diffuser
Luminaire light beam spread	-

Operating and Electrical	
Input Voltage	220 to 240 V
Line Frequency	50 or 60 Hz
Power Consumption	19 W
Power Factor (Fraction)	0.9
Temperature	
Ambient temperature range	0 to +45 °C
Controls and Dimming	
Dimmable	Yes
Control interface	DALI
Mechanical and Housing	
Housing Material	Aluminum extruded
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Housing Color	Aluminum and gray
Mounting device	Mounting bracket

Pureline Slim EX

Optical cover/lens shape	Flat
Overall length	1,194 mm
Overall width	74 mm
Overall height	78.5 mm
Dimensions (Height x Width x Depth)	79 x 74 x 1194 mm
Material	Aluminum

Approval and Application

Ingress protection code	IP20 [Finger-protected]
Mech. impact protection code	IK02 [0.2 J standard]
Surge Protection (Common/Differential)	Surge protection level until 2 kV
Protection class IEC	Safety class I

Initial Performance (IEC Compliant)

Initial chromaticity	<5
----------------------	----

Power consumption tolerance	+/-10%
-----------------------------	--------

Over Time Performance (IEC Compliant)

Median useful life L70B50	50,000 hour(s)
---------------------------	----------------

Product Data

Order product name	RC780X LED22S-6500 PSD W6L120 OD SI EX
Order code	919515898143
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	919515898143
Full product name	RC780X LED22S-6500 PSD W6L120 OD SI EX

Dimensional drawing

Installation Instructions PHILIPS PURELINE SLIM RECESSED

220-240V~ 50/60 Hz IP20 IEC Exempted 4000lm

TYPE	A	B	Voltage	Frequency
RC780X LED22S-6500	78	88	220-240V~	50/60Hz
RC780X LED22S-6500	88	98	220-240V~	50/60Hz
RC780X LED22S-6500	98	108	220-240V~	50/60Hz
RC780X LED22S-6500	108	118	220-240V~	50/60Hz
RC780X LED22S-6500	118	128	220-240V~	50/60Hz
RC780X LED22S-6500	128	138	220-240V~	50/60Hz
RC780X LED22S-6500	138	148	220-240V~	50/60Hz
RC780X LED22S-6500	148	158	220-240V~	50/60Hz
RC780X LED22S-6500	158	168	220-240V~	50/60Hz
RC780X LED22S-6500	168	178	220-240V~	50/60Hz
RC780X LED22S-6500	178	188	220-240V~	50/60Hz
RC780X LED22S-6500	188	198	220-240V~	50/60Hz
RC780X LED22S-6500	198	208	220-240V~	50/60Hz
RC780X LED22S-6500	208	218	220-240V~	50/60Hz
RC780X LED22S-6500	218	228	220-240V~	50/60Hz
RC780X LED22S-6500	228	238	220-240V~	50/60Hz
RC780X LED22S-6500	238	248	220-240V~	50/60Hz
RC780X LED22S-6500	248	258	220-240V~	50/60Hz
RC780X LED22S-6500	258	268	220-240V~	50/60Hz
RC780X LED22S-6500	268	278	220-240V~	50/60Hz
RC780X LED22S-6500	278	288	220-240V~	50/60Hz
RC780X LED22S-6500	288	298	220-240V~	50/60Hz
RC780X LED22S-6500	298	308	220-240V~	50/60Hz
RC780X LED22S-6500	308	318	220-240V~	50/60Hz
RC780X LED22S-6500	318	328	220-240V~	50/60Hz
RC780X LED22S-6500	328	338	220-240V~	50/60Hz
RC780X LED22S-6500	338	348	220-240V~	50/60Hz
RC780X LED22S-6500	348	358	220-240V~	50/60Hz
RC780X LED22S-6500	358	368	220-240V~	50/60Hz
RC780X LED22S-6500	368	378	220-240V~	50/60Hz
RC780X LED22S-6500	378	388	220-240V~	50/60Hz
RC780X LED22S-6500	388	398	220-240V~	50/60Hz
RC780X LED22S-6500	398	408	220-240V~	50/60Hz
RC780X LED22S-6500	408	418	220-240V~	50/60Hz
RC780X LED22S-6500	418	428	220-240V~	50/60Hz
RC780X LED22S-6500	428	438	220-240V~	50/60Hz
RC780X LED22S-6500	438	448	220-240V~	50/60Hz
RC780X LED22S-6500	448	458	220-240V~	50/60Hz
RC780X LED22S-6500	458	468	220-240V~	50/60Hz
RC780X LED22S-6500	468	478	220-240V~	50/60Hz
RC780X LED22S-6500	478	488	220-240V~	50/60Hz
RC780X LED22S-6500	488	498	220-240V~	50/60Hz
RC780X LED22S-6500	498	508	220-240V~	50/60Hz
RC780X LED22S-6500	508	518	220-240V~	50/60Hz
RC780X LED22S-6500	518	528	220-240V~	50/60Hz
RC780X LED22S-6500	528	538	220-240V~	50/60Hz
RC780X LED22S-6500	538	548	220-240V~	50/60Hz
RC780X LED22S-6500	548	558	220-240V~	50/60Hz
RC780X LED22S-6500	558	568	220-240V~	50/60Hz
RC780X LED22S-6500	568	578	220-240V~	50/60Hz
RC780X LED22S-6500	578	588	220-240V~	50/60Hz
RC780X LED22S-6500	588	598	220-240V~	50/60Hz
RC780X LED22S-6500	598	608	220-240V~	50/60Hz
RC780X LED22S-6500	608	618	220-240V~	50/60Hz
RC780X LED22S-6500	618	628	220-240V~	50/60Hz
RC780X LED22S-6500	628	638	220-240V~	50/60Hz
RC780X LED22S-6500	638	648	220-240V~	50/60Hz
RC780X LED22S-6500	648	658	220-240V~	50/60Hz
RC780X LED22S-6500	658	668	220-240V~	50/60Hz
RC780X LED22S-6500	668	678	220-240V~	50/60Hz
RC780X LED22S-6500	678	688	220-240V~	50/60Hz
RC780X LED22S-6500	688	698	220-240V~	50/60Hz
RC780X LED22S-6500	698	708	220-240V~	50/60Hz
RC780X LED22S-6500	708	718	220-240V~	50/60Hz
RC780X LED22S-6500	718	728	220-240V~	50/60Hz
RC780X LED22S-6500	728	738	220-240V~	50/60Hz
RC780X LED22S-6500	738	748	220-240V~	50/60Hz
RC780X LED22S-6500	748	758	220-240V~	50/60Hz
RC780X LED22S-6500	758	768	220-240V~	50/60Hz
RC780X LED22S-6500	768	778	220-240V~	50/60Hz
RC780X LED22S-6500	778	788	220-240V~	50/60Hz
RC780X LED22S-6500	788	798	220-240V~	50/60Hz
RC780X LED22S-6500	798	808	220-240V~	50/60Hz
RC780X LED22S-6500	808	818	220-240V~	50/60Hz
RC780X LED22S-6500	818	828	220-240V~	50/60Hz
RC780X LED22S-6500	828	838	220-240V~	50/60Hz
RC780X LED22S-6500	838	848	220-240V~	50/60Hz
RC780X LED22S-6500	848	858	220-240V~	50/60Hz
RC780X LED22S-6500	858	868	220-240V~	50/60Hz
RC780X LED22S-6500	868	878	220-240V~	50/60Hz
RC780X LED22S-6500	878	888	220-240V~	50/60Hz
RC780X LED22S-6500	888	898	220-240V~	50/60Hz
RC780X LED22S-6500	898	908	220-240V~	50/60Hz
RC780X LED22S-6500	908	918	220-240V~	50/60Hz
RC780X LED22S-6500	918	928	220-240V~	50/60Hz
RC780X LED22S-6500	928	938	220-240V~	50/60Hz
RC780X LED22S-6500	938	948	220-240V~	50/60Hz
RC780X LED22S-6500	948	958	220-240V~	50/60Hz
RC780X LED22S-6500	958	968	220-240V~	50/60Hz
RC780X LED22S-6500	968	978	220-240V~	50/60Hz
RC780X LED22S-6500	978	988	220-240V~	50/60Hz
RC780X LED22S-6500	988	998	220-240V~	50/60Hz
RC780X LED22S-6500	998	1008	220-240V~	50/60Hz

Product Dimensions 2 Feet

Product Dimensions 4 Feet

ATTENTION: Install by a qualified electrician and wired in accordance with local NEC electrical regulations or the national requirements.

