



Tango G2 LED

BVP282 LED252/NW 200W 220-240V SWB

Tango G2 LED is a general purpose LED flood lighting luminaire for various lighting applications, such as area lighting, bill-board, façade, industry area, recreational sports and other general applications. The Tango G2 LED flood light incorporates LED light source, optical system, heat sink and driver into one compact housing. Its specially designed heat sink incorporates aesthetics and functionality to ensure reliability and long lifetime. Tango G2 LED takes advantage of LED technology which provides energy savings and a longer lifetime, bringing area lighting into a new era.

Product data

General Information		Constant light output	
Lamp family code	-	Number of products on MCB (16 A type B)	-
Lamp colour code	Neutral white	EU RoHS compliant	No
Light source replaceable	Yes	Light source engine type	LED
Number of gear units	-	Serviceability class	-
Driver/power unit/transformer	PSU [Power supply unit]	Light Technical	
Driver included	Yes	Standard tilt angle post-top	-
Optical cover/lens type	PC-MLO [Polycarbonate micro lens optic]	Standard tilt angle side entry	-
Luminaire light beam spread	100°	Operating and Electrical	
Control interface	-	Input Voltage	220-240 V
Connection	Flying leads/wires	Input frequency	50 or 60 Hz
Cable	Cable 1.5 m without plug (C1K5)	Initial CLO power consumption	- W
Protection class IEC	Safety class I (I)	Average CLO power consumption	- W
Flammability mark	NO [-]	End CLO power consumption	- W
CE mark	CE mark	Power factor (min.)	0.95
ENEC mark	-		
Warranty period	3 years		
Optic type outdoor	Symmetrical wide beam		

Tango G2 LED

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Housing material	Aluminum die-cast
Reflector material	-
Optic material	Polycarbonate
Optical cover/lens material	Polycarbonate
Fixation material	Steel
Mounting device	MBA [Mounting bracket adjustable]
Optical cover/lens shape	-
Optical cover/lens finish	Frosted
Overall length	655 mm
Overall width	480 mm
Overall height	60 mm
Effective projected area	0.25 m ²
Colour	Aluminium and Grey

Approval and Application

Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [2 J reinforced]
Surge protection (common/differential)	Surge protection level until 10 kV

Initial Performance (IEC Compliant)

Initial luminous flux	25200 lm
-----------------------	----------

Luminous flux tolerance	+/-10%
Initial LED luminaire efficacy	125 lm/W
Lamp colour temperature	4000 K
Colour Rendering Index	70
Initial chromaticity	SDCM<=7
Initial input power	200 W
Power consumption tolerance	+/-10%

Application Conditions


Ambient temperature range	-40 to +50 °C
---------------------------	---------------

Product Data

Full product code	911401664504
Order product name	BVP282 LED252/NW 200W 220-240V SWB
Order code	911401664504
SAP numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401664504
SAP net weight (piece)	11.799 kg



Dimensional drawing



BVP281-BVP284 Tango LED gen2

Tango G2 LED

