



ZXP399 DMX Controls and Accessories

ZXP399 main controller DMX/RDM

90 to 264 V - 50 to 60 Hz - Finger-protected - CE mark - Black

The ZXP399 DMX Controls and Wiring Accessories are to be used with our architectural and facade lighting luminaires (UniFlood C, M and G, UniStrip G4, UniEdge, UniDot G2, UniString and UniBar).;DMX Controls include a main controller, stand-alone controller, sub-controllers, DMX amplifier and DMX addressing device.;Main Controller: Industrial computer that can control up to 6,000 DMX universes.;Stand-alone Controller: Fits all medium applications with up to 700 DMX universes.;Wiring accessories include leader and jump cables with male and female IP67 connectors and end-caps.;Addressing Device: Hand-held device that can write DMX addresses to a whole run on-site within minutes.;DMX Amplifier: Compact, IP65 and low-power repeater that can amplify the DMX signal for up to 100 metres.

Product data

General Information	
CE mark	CE mark
Colour	Black
Operating and Electrical	
Input Voltage	90 to 264 V
Input frequency	50 to 60 Hz
Mechanical and Housing	
Overall length	482 mm

Overall width	361 mm
Overall height	177 mm
Dimensions (height x width x depth)	177 x 361 x 482 mm (7 x 14.2 x 19 in)
Approval and Application	
Ingress protection code	IP20 [Finger-protected]
Product Data	
Full product code	911401756622
Order product name	ZXP399 main controller DMX/RDM


ZXP399 DMX Controls and Accessories

Order code	911401756622
Numerator – quantity per pack	1
Numerator – packs per outer box	1
SAP material	911401756622

SAP net weight (piece)	11.649 kg
------------------------	-----------



Dimensional drawing



ZXP399

